TOUCH DYNAMIC

PR-TB-650II



Reliable Compact printer

The PR-TB-650II features the best of both worlds by coupling the comfort of legacy products with the speed and connection demanded today in hospitality environments. The PR-TB-650II features low cost and high performance combined with the ability to work effectively in any environment. Out of the box, the PR-TB-650II can easily be configured. New vertical mounting stand and splash proof cover options help make it one of the most reliable POS printers in the world.

With its "drop in and print" paper loading, small footprint and reliable guillotine cutter, the PR-TB-650II is a welcomed addition to POS systems. The TSP650II is ideal for retail establishments and restaurants. Demand everything from your receipt printer.



Highlights

• Small footprint

High Speed: 300mm/sec

• Highly reliable auto cutter

"Drop in & Print" paper loading

WebPRNT interface available

• Serial, parallel, USB, Ethernet, Bluetooth,



PR-TB-650II

TOUCH DYNAMIC



| Features – Hardware: | Fast: 60 RPM (300mm/s) |
|---------------------------|--|
| | Reliable Guillotine Cutter |
| | Horizontal and Vertical Use |
| | Drop-In and Print Paper Loading |
| | |
| | Logo Utility (Store Logos, Coupons, and Graphics) |
| | Swappable Communication Interface (Excluding Bluetooth Model) |
| | Recessed Cable Connections |
| | StarlO SDK Available |
| Connectivity: | Serial, Parallel, USB, Ethernet, Bluetooth, WebPRNT |
| Operating System Support: | Windows [®] 7 32/64 Bit, Vista 32/64 Bit, XP 32 Bit, XP Embedded, CE, |
| | Server 2008 32/64 Bit, OPOS™, JavaPOS™, Virtual Serial Port, |
| | Linux™ CUPS, Mac OS X CUPS, StarIO SDK |
| What's included: | Installation CD (Printer Driver / Manuals) |
| | Setup Guide |
| | Wall Mount Bracket |
| | Vertical Mount Pads |
| | 58mm Paper Guide |
| | Power Switch Cover |
| | Start-up Paper Roll |
| | External Power Supply |
| Options: | Splash Proof Cover (SPC-T100) |
| | Integrated Buzzer (BU01-24-A) |
| | Vertical Stand (VS-T650) |
| | White* or Gray Color Housing |
| | *(White Color Housing only available for Parallel, USB, Ethernet, |
| | Bluetooth and WebPRNT models only) |
| Technical Specifications: | |
| Print Method | Direct Thermal |
| Print Resolution | 203 dpi |
| Print Speed | 300mm/second |
| Paper Width | 80mm / 58mm |
| Paper Thickness | 0.053 – 0.085mm |
| Paper Roll Diameter | 83mm |
| Dimensions | 140 (W) x 132 (H) x 203.5 (D) mm |
| Reliability: | |
| Printer MCBF | 60 million lines |
| Cutter | 2 million cuts |
| | |





