

TOUCH DYNAMIC

Epson T20



Highlights

- Printing up to 150mm/sec
- Integrated power supply
- Ease-of-use features including drop-in paper loading, autocutter and status LEDs
- Low power consumption, ENERGY STAR qualified.
- Interface cable Included in the box
- Wallmount bracket included in the box
- Epson reliability

Epson's cost-effective ReadyPrint T20 thermal printer is the latest addition to Epson's line of energy-efficient POS Printers. Designed to deliver Epson's renowned reliability in harsh environments while maintaining a cost effective solution. The Epson T20 combines basic POS printing functionality with high reliability and multiple ease-of-use features.

The Epson T20 comes with multiple ease-of-use features including drop in paper loading, autocutter, status LEDs and more. And it also offers versatile printer placements including horizontal or upright for front receipt dispensing or vertical placement using a mounting bracket.

The Epson T20 has a MCBF of 60 million lines, a MTBF of 360,000 hours and an autocutter of 1.5 million cuts. The Epson T20 delivers the reliability customers expect from Epson and Touch Dynamic.



General	
Print Method	Thermal line printing
Print Font	Font 9x17 and 12x24 dots/char (WxH)
	Column capacity Standard; Paper width 80mm: 48x64; Paper width 58mm 35/46 42 column mode; Paper width 80mm 42/60; Paper width 58mm: 42/31
	Character size 0.88 x 2.13 and 1.25 x 3 mm (W x H)
	Character set 95 Alphanumeric, 18 set International, 128 x 43 graphic. Barcode: UPC-A, UPC-E, JAN 13 (EAN13), JAN8 (EAN); CODE39, ITF, CODABAR (NW-7), CODE93, CODE128, GS1-128, GS1 DataBar. Two-dimensional code: PDF417, QRCode, Maxi-Code, 2D GS1 DataBar, Composite Symbology
	Characters per inch 22.6 and 16.9 cpi
Printer	
Interface	USB, Serial, Ethernet
Print Speed	Max 150 mm/sec (5.91in/sec)
Paper Dimension	80mm: 3.13" ± 0.02" x 3.27" diameter (79.5 ± 0.5(W) x 83mm) 58mm: 2.26" ± 0.02" x 3.27" diameter (57.5 ± 0.5(W) x 83mm)
Power	100 - 240 AC, 50/60Hz
Power Consumption	Approx. 1.0A
Power Supply	Internal (AC cable included)
D.K.D. Function	2 drivers
Reliability	MTBF - 360,000 hours MCBF - 60,000,000 lines
Overall Dimensions	5.51" x 7.83" x 5.75" (140 x 199 x 146mm) (W x D x H)
Weight	3.75lb (1.7kg)
Color	Epson Dark Gray
Standard Accesories	Roll paper x 1 roll ((for checking the initial movement of the printer), CD-ROM, power switch cover, power switch waterproof cover, wall hanging bracket, screws for wall hanging bracket, rubber feet for vertical installation, switch panel for vertical installation, 58mm width paper guide plate, interface cable, AC cable
Safety Standard	UL/CSA/EN/TUV/GOST-R
CD ROM Contents	Drivers & tool software (APD, OPOS™, JavaPOS™, OPOS NET™, TM Virtu-al port driver, Linux® Cups driver, Mac OS® X driver, ReadyPrint T20 Utility, EpsonNet Simple Viewer), Manuals (ReadyPrint T20 user's manual, ReadyPrint T20 software manual)
Installation	Horizontal/vertical on counter/vertical on wall with wall hanging bracket

