



TB3 Trio Thermal Printer



Features

- Direct Thermal
- Drop in Paper Loading
- High Speed Printing (200mm/s)
- Bar Code Printing
- Epson Compatible

3-in-1 Interface Includes:

- Serial
- Ethernet
- USB

The TB3 Trio is Touch Dynamic's latest version of the reliable TB3 Printer Series. The TB3 Trio features three interface's on each printer including Serial, USB and Ethernet. The triple interface enables customers to stock one product and meet all their roll out needs. The TB3 Trio boasts Jam Free Auto Cutter technology to deliver an extremely reliable printer solution.



TB3 Trio Thermal Printer

TOUCH
DYNAMIC

| TB3 Trio Specifications | | |
|--------------------------|-------------------------|---|
| Print method | | Direct Thermal |
| Print speed | | 200mm/sec |
| Print buffer | | 4K (can be increased to 12K on special order) |
| Resolution | | 180dpi x 180dpi |
| Dot pitch | | 0.141mm x 0.141mm |
| Effective printing width | | 72mm, 512 dots/line |
| Printing direction | | Unidirectional with friction feed |
| Character per line | | Font A (12x24) 42 columns Font B (9x17) 58 columns |
| Paper | Type | Thermal paper |
| | Width | 50mm ~ 82.5mm (2in ~ 3.5in) |
| | Thickness | 0.06 ~ 0.09mm |
| | Roll diameter | Max 80mm (3.5in) |
| Reliability | Tph life | 160Km |
| | Mcbf | 60,000,000 lines |
| Character set | Alphanumeric character | 95 |
| | Extended graphic | 128x18 page |
| | International character | 14 |
| Barcode | | EAN-8, EAN-13, CODE39, ITF, UPC-A, CODEBAR, CODE 93, CODE 128, PDF417(20) |
| Emulation | | ESC/POS COMMAND COMPATIBLE |
| Drawer port | | 1 port |
| Interfaces included | | Serial, USB, Ethernet |
| Power | Type | External SMPS |
| | AC | 100-240V 50/60Hz |
| | DC | 24Vdc / 1.75A |
| Dimension | WxDxH | 6.3x8.5x6.25 in |
| Weight | Includes auto cutter | 3.75lbs |

