

EC150 Touch Monitor



Highlights:

- Sleek and Stylish design
- Resistive Touch
- Smart Cable Management
- Detachable Stand / Supports VESA Mounting
- Spill Proof & Anti-Dust
- Dual Input VGA or DVI
- Dual Interface Touch - USB or Serial

Integrated Options:

- 3 Track USB MSR
- 2x20 Rear Customer Display

Attractive, High Quality Touch Monitor

The EC150 is a reliable touch monitor with a sleek look. The EC150 boasts a dual interface resistive touch screen. The EC150 supports an integrated front facing 3 Track USB MSR. It also supports an integrated 2x20 rear customer display. The EC150 supports all of this with smart cable management. The EC150 is a high quality touch monitor that delivers a great value to the customer.





Display

- Display Size - 15"
- Optimal Resolution - 1024 x 768
- Panel Brightness - 250 cd/m2 (typical)
- Contrast Ratio - 600:1

External I/O

- Serial Ports - 2 (1x DB9 RS-232, 1x RJ45 for 2x20 Rear Customer Display)
- USB - 2x USB out, 1x USB in (B type)
- Video - 1x VGA (D-SUB 15pin), 1x DVI-D
- Controls - 5x OSD buttons, status LED

Characteristics

- Response Time - 8ms (typical)
- Tile Angle - 0° - 70°
- Viewing Angle - 160°

Environment

- Operating Temperature - 0°F ~ 40°F
- Storage Temperature - 10°F ~ 50°F
- Operating Humidity - 20% ~ 80% RH non condensing
- Storage Humidity - 10% ~ 90% RH non condensing

Input

- Input Video Signal - VGA & DVI
- Touch Function - USB or RS232

Dimension

- Dimension - 14.4(W) x 13.3(H) x 7.9(D)
- Weight - 10.3lbs(net)

Power

- Power Consumption- 20W operation / 3W standby
- Input Frequency - Horizontal 31.5 - 60.2KHz; Vertical 56.3 - 75Hz
- Power Supply - DC 12V +/- 10%

Optional

- 3 Track USB MSR
- 2x20 Rear Customer Display

