



# Pulse J1900 All-In-One



**Pulse J1900 AIO**  
Projected Capacitive Touch  
MSR and Fingerprint Reader



**Pulse J1900 AIO**  
Projected Capacitive Touch  
with Universal Printer Base  
and T70II Printer



**Pulse J1900 AIO**  
with Universal Printer Base  
and 8" Rear LCD

## Highlights

- Intel Celeron Quad Core J1900 2.0Ghz
- 15" LCD with Projected Capacitive Touch Screen
- Fanless - Ideal for Harsh Environments
- Up to 8G DDR3
- Wall Mountable, VESA 100x100

## Optional Peripherals

- Integrated MSR
- Integrated Fingerprint Reader
- Integrated 2x20 VFD, 8", 12" or 15" Rear LCD
- Integrated 2D Barcode Scanner

The Pulse J1900 All-In-One system is designed to offer speed and reliability at an affordable price.

The Pulse J1900 All-In-One boasts a quick detachable base and easy overall service features. A 15" LCD with Projected Capacitive Touch Screen and up to 8GB of RAM, this fanless system is ideal for harsh environments and can accommodate your application needs.

The Pulse J1900 All-In-One offers a variety of add-on options including, integrated MSR or MSR/URU Biometric Reader, a 2 x 20 VFD customer display and an integrated rear 8", 12", or 15" Rear LCD.



<b>Processing</b>	
CPU	Intel Celeron Dual Core J1900 2.0GHz (up to 2.42GHz)
Chipset	J1900 SOC
System Memory	1 x DDR3 DIMM 2GB, 4GB or 8GB Optional
Graphic Memory	Intel HD Graphics, DX11
<b>LCD Panel</b>	
LCD Size	15"
LCD Type	LED LCD
Brightness	250 nits
Maximum Resolution	1024 x 768
Touch Screen Type	Projected Capacitive (USB Interface)
Tilt Angle	0° ~ 140°
Screen	BezelLess True Flat
<b>Storage</b>	
HDD	One 2.5" SATA HDD, SSD or Compact Flash
<b>Power</b>	
Power Supply	65W 19V power adapter
EMC & Safety	FCC / CE Class A, LVD
Operating Temperature	5°C ~ 35°C (41°F ~ 95°F)
<b>Dimensions</b>	
15" w Base & MSR	13.6" H x 16.9" W x 9.9" D
<b>Expansion</b>	
Mini-PCIe Slot	1
<b>I/O Ports</b>	
USB	4 (USB 2.0) 1 (USB 3.0)
Serial	3 x RJ45 with DB9 Adapters (COM3,4 p-owered with 5V/12V, by jumper)
Gigabit LAN (10/100/1000)	1
Cash Drawer Port	1 RJ11 (12V / 24V)
DC Jack	1
Power Button	1
PS/2	1 (Optional)
Audio Out	1 Set (Optional)
<b>Optional Peripherals</b>	
MSR USB	Encrypted Option Available
Fingerprint Reader	Digital persona, URU (USB interface)
Rear LCD	8.4", 12.1" or 15"
Customer Display	2 x 20 VFD Display
Wireless LAN	802.11 a/b/g/n
Scanner	2D Barcode Scanner
<b>OS Support</b>	
	POS Ready 7, Windows 7 (32bit and 64 bit), Windows Embedded Industrial Retail, Windows 8.1 Pro (64bit), Windows 10 Pro (64 bit), Windows 10 IOT (64 bit)

