

TOUCH DYNAMIC

Epson TM-T70II



Highlights

- Unique Design:
Fully Front operated it fits under or on the counter
- Splash proof housing:
Ideal for the rough hospitality environment
- High Print speed:
Doesn't let customers wait
- Robust and reliable: Saves cost for maintenance and service
- Universal Printer Base compatible

The first PoS printer with front-facing controls, the TM-T70 is specifically designed for under counter operations in retail and hospitality. With a range of core, user-friendly features including front paper feeding with drop-in paper rolls, auto-cutter, remote maintenance counter and easy access operator covers, the TM-T70 enables fast, easy transactions and enhanced customer service. Offering the high quality and reliability of Epson's world renowned TM-T88 series, the TM-T70 has advanced text, graphics and barcode print-ing capability. Unlike many other printers, the TM-T70 boasts the same quiet, high, print speed for both text and graphics. The compact TM-T70 includes an external rear splash cover for increased spill resistance, enhanced cable management system and full auto status back reporting.

The TM-T70 benefits from new drivers including OPoS ADK, Java and Win APD and is equipped with a range of interface options including parallel, serial, USB version 2, powered USB, ethernet and wireless for seamless integration with existing retail systems.

Fully compatible with Touch Dynamic's Universal Printer Base.



Epson TM-T70II

TOUCH
DYNAMIC

| Thermal Printer | |
|-------------------|--|
| Print Method | Thermal Line Printing |
| Print Speed Paper | Max. 250mm/sec |
| Dimensions | 80mm: 3.13" ± 0.02" x 3.27" diameter (79.5 ± 0.5(W)x 83mm) |

| Reliability | |
|-------------|------------------|
| MTBF | 14.1" Widescreen |
| MCBF | 1366 x 768 |
| Autocutter | 200 cd/m2 |

| General Information | |
|----------------------|---|
| Interface | Built-in USB interface + another selection: serial or parallel |
| Power | 1100-240V AC, 50/60Hz |
| Power consumption | Approx 2.0A (mean) |
| Power supply | External power by the Universal Printer Base |
| Dimensions | 4.92" x 7.64" x 4.49" (125 x 194 x 114mm) |
| Weight | 3.75LBS (1.7Kg) |
| Color | Black |
| Printer Base support | Yes |
| Driver support | OPOSTM, JavaPOSTM, OPOS NETTM, TM Virtual COM, Linux, Cups driver, MAC OS X driver, Posready09, Posready7, Windows 7 Pro, Windows 8.1 Pro, Windows 8.1 Embedded Industry Retail (APD) |

