



BREEZE TOUCH MONITOR



Highlights

- Serial and USB Touch Interface
- External Power Supply, Hidden in Base
- Excellent Cable Management
- Projected Capacitive Touch
- Internal Speakers
- Available in 15" or 17"

Options

- Integrated MSR 3 tracks, PS/2 or USB Interface
- Integrated Fingerprint Reader
- Rear Customer Display options include: 8", 12", 15" & 2x20

Designed to provide enhanced computing performance and versatility, the Breeze Touch Monitor comes in Serial and USB Touch interface. It has an external power supply which is hidden in base. It provides an excellent solution for cable management.



BREEZE TOUCH MONITOR

TOUCH
DYNAMIC

LCD Panel	
LCD Size	15" or 17"
Brightness	250 nits
Max. Resolution	15": 1024x768, 17": 1280x1024
Touch Screen Type	Projected Capacitive Touch
Tilt Angle	0° - 70°

External I/O	
VGA	1
Serial Ports	2 (1xDB9 RS-232, 1xRJ45 out for VFD)
USB	1 x USB out, 1 x USB in (B Type)
On Screen Display Button	2
PS/2	1

Peripheral Options	
MSR	3 tracks (PS/2 or USB interface)
Customer Display	2 x 20 VFD (COM)
Speakers	2 x 2 watt internal speaker

Power Adapter	
Power Supply	36W (12V / 3A max)

Environment	
EMC & Safety	FCC/CE Class A, LVD
Operating Temperature	41°F - 113°F
Storage Temperature	4°F - 140°F
Operating Humidity	5% - 95% non condensing
Storage Humidity	5% - 95% non condensing
Dimensions	LCD 14.7 x 10 x 14.5 W/Base: 16.85 x 13.45 x 9.9
Weight	15Lbs
Mounting	100 x 100 VESA mount

