



Touch Dynamic PR-IM



Touch Dynamic TB3 Trio



Touch Dynamic TB4

PR-IM HIGHLIGHTS

- ☆ Clamshell design for easy paper loading
- ☆ Spill-proof and heat resistant
- ☆ 2-color, high quality graphics
- ☆ Swappable interface available

TB4 HIGHLIGHTS

- ☆ Dual interface options
- ☆ Wall mountable
- ☆ Drop in paper loading
- ☆ Epson compatible

TB3 TRIO HIGHLIGHTS

- ☆ 3-in-1 interface
- ☆ Barcode printing
- ☆ High speed printing (200mm/sec)
- ☆ Epson compatible



SPECIFICATIONS

IMPACT RECEIPT PRINTER

Print Method: 9 Pin Impact Dot Matrix Print
 Print Speed: 13 RPM (receipts per minute), (4.7 LPS)
 Paper Width: (standard) 70 & 58mm (with paper guide)
 Dimensions: 6.3" x 6" x 9.7" (WxHxD)
 Weight: 4Lbs
 Emulation: Star Mode, ESC/POS
 Cutter: 1 million cuts
 MCBF: 22 million lines

INTERFACE

Parallel, USB, Ethernet, Wi-Fi

OPTIONAL ACCESSORIES

Kitchen Buzzer Wall, Mount Brackets

DRIVER SUPPORT

Windows, 98, ME, NT 4.0, WePOS, 2000, XP, CE, XP Embedded VISTA (32- and 64 bit), OPOS, Java POS, Linus, Mac OSX

SPECIFICATIONS

THERMAL PRINTER

Print Method: Direct Thermal
 Print Speed: 200mm/sec
 Dimensions: 6.3" x 6.25" x 8.5" (WxHxD)
 Weight: 3.75Lbs
 Cutter: 1 million cuts
 Emulation: ESC/POS Command Compatible
 Paper Width: 50mm ~ 82.5mm (2in ~ 3.5in)
 Barcode: EAN-8, EAN-13, CODE39, ITF, UPC-A, CODEBAR, CODE 93, CODE 128, PDF417(20)
 Drawer Port: 1 Port

INTERFACE

Serial, USB, Ethernet

SPECIFICATIONS

THERMAL PRINTER

Print Method: 8x8 dots / 203DPI
 Print Speed: Max 250mm/sec
 Dimensions: 6.3" x 6.78" x 9.46" (WxHxD)
 Weight: 1.4Kg (3Lbs)
 Cutter: 1 million cuts
 Emulation: ESC/POS Mode, OPOS
 Paper Width: 79.6mm / 57.7mm
 Cover Upon Sensor: Mechanical Sensor
 NE Sensor: Translation Sensor
 Wall Mounted Chassis: Wall Mount-Bracket included

INTERFACE

Serial+USB / Parallel+USB / Ethernet+USB

DRIVER SUPPORT

Windows Xp SP3 or later 32-bit, Windows Vista 32/64-bit SP2 or later, Windows 7 32/64-bit, POSReady 2009

