



HIGHLIGHTS



True Flat Resistive Touch Screen



Serial and USB Touch Interface



Available in 15" or 17"



Internal Speakers



Multiple Periphral Options Include: MSR, Fingerprint Reader, Customer Display, and Universal Printer Base

SPECIFICATIONS

DISPLAY

LCD Size: 15" or 17"

Brightness: 250 nits

Max. Resolution: 1024x768 (15"), 1280x1024 (17")

Touch Screen Type: True Flat Resistive Touch

Tilt Angle: 0° - 70°

EXTERNAL I/O PORTS

VGA: 1

Serial Ports: 2 (1xDB9 RS-232, 1xRJ45 out for VFD)

USB: 1 x USB out, 1 x USB in (B Type)

On Screen Display Button: 2

PS/2: 1

PERIPHERAL OPTIONS

MSR: 3 tracks (PS/2 or USB interface)

Customer Display: 2 x 20 VFD (COM)

Speakers: 2 x 2 watt internal speaker

POWER ADAPTER

Power Supply: 36W (12V / 3A max)

ENVIRONMENT

EMC & Safety: FCC/CE Class A, LVD

Operating Temperature: 41°F - 113°F

Storage Temperature: 4°F - 140°F

Operating Humidity: 5% - 95% non condensing

Storage Humidity: 5% - 95% non condensing

Dimensions: LCD 14.7 x 10 x 14.5, with base: 16.85 x 13.45 x 9.9

Weight: 15Lbs

Mounting: 100 x 100 VESA mount



KEY FEATURES

1	Projected Capacitive Touch Screen
2	Serial and USB Interface
3	Internal Speakers
4	External Power Supply (Hidden in Base)
5	Available in 15" and 17"