



Epson T20



Epson TM-T70II



Epson TM-M30

T20 HIGHLIGHTS

- ☆ Epson reliability
- ☆ Printing up to 150mm/sec
- ☆ Integrated power supply
- ☆ Interface cable included in the box

TM-M30 HIGHLIGHTS

- ☆ Sleek, compact and stylish design
- ☆ Direct printing from web browsers
- ☆ NFC and QR code pairing
- ☆ ePOS-Print allows direct printing from any mobile devices
- ☆ Available in black or white

TM-T70II HIGHLIGHTS

- ☆ Fully front operated, fits under or on the counter
- ☆ Splash proof housing
- ☆ High print speed
- ☆ Robust and reliable



SPECIFICATIONS

THERMAL PRINTER

Print Method: Thermal Line Printing

Print Speed Paper: Max. 150mm/sec

Dimensions: 80mm: 3.13" ± 0.02" x 3.27" diameter (79.5 ± 0.5(W) x 83mm)

58mm: 2.26" ± 0.02" x 3.27" diameter (57.5 ± 0.5(W) x 83mm)

RELIABILITY

MTBF: 360,000 hours

MCBF: 60,000,000 lines

Autocutter: 200 cd/m²

GENERAL INFORMATION

Interface: USB, Serial, Ethernet

Power: 100-240 AC, 50/60Hz

Power Consumption: Approx 1.0A

Power Supply: Internal (AC cable included)

Dimensions: 5.51" x 7.83" x 5.75" (140 x 199 x 146mm) (W x D x H)

Weight: 3.75LBS

Color: Epson Dark Gray

Printer Base Support: No

Driver Support: APD, OPOST™, JavaPOS™,

OPOS NET™, TM Virtual port driver, Linux

Cups® driver, Mac OS® X driver, ReadyPrint

T20 Utility, EpsonNet Simple Viewer

SPECIFICATIONS

THERMAL PRINTER

Print Method: Thermal Line Printing

Print Speed Paper: Max. 250mm/sec

Dimensions: 80mm: 3.13" ± 0.02" x 3.27" diameter (79.5 ± 0.5(W) x 83mm)

RELIABILITY

Autocutter: 200 cd/m²

GENERAL INFORMATION

Interface: Built-in USB interface + another selection: serial or parallel

Power: 1100-240V AC, 50/60Hz

Power Consumption: Approx 2.0A (mean)

Power Supply: External power by the Universal Printer Base

Dimensions: 4.92" x 7.64" x 4.49" (125 x 194 x 114mm)

Weight: 3.75LBS

Color: Black

Printer Base Support: Yes

Driver Support: OPOST™, JavaPOS™, OPOS

NET™, TM Virtual COM, Linux Cups driver,

MAC OS® X driver, Posready09, Posready7,

Windows 7 Pro, Windows 8.1 Pro, Windows

8.1 Embedded Industry Retail (APD)

SPECIFICATIONS

THERMAL PRINTER

Print Method: Thermal Line Printing

Print Speed Paper: Max. 200mm/sec

Roll Diameter: 83mm

Paper Loading: Drop-in

RELIABILITY

MCBF: 15 million lines

Autocutter: 1.5 million cuts

GENERAL INFORMATION

Interface: Ethernet, Bluetooth, Wi-Fi (USB connectivity available on Ethernet and Bluetooth models)

Dimensions: 127 x 127 x 127mm

Weight: 2.8 LBS

Color: Epson Black, Epson Ultra White

Printer Base Support: Yes

OS: iOS, Android, Windows

Driver Support: ePOS-Print SDK, OPOS ADK,

OPOS ADK for .net, JavaPOS ADK, Epson

EDP, Mac Driver



Epson TM-U220



Epson Mobilink P20



Epson TM-T88

TM-U220 HIGHLIGHTS

- ☆ Flexible paper width
- ☆ Drop-in paper load
- ☆ Autocutter included
- ☆ High-speed printing

TM-T88 HIGHLIGHTS

- ☆ Compatible with Android and Windows mobile devices
- ☆ Easy IP/network configuration
- ☆ Fast printing
- ☆ Easy to configure and install

Mobilink P20 HIGHLIGHTS

- ☆ Compatible with iOS, Android and Windows mobile devices
- ☆ Highest printing speed in its class of up to 100mm/second
- ☆ Best-in-class operational battery life for ultra compact prints of up to 8 hours
- ☆ Couples with the Touch Dynamic Windows Quest Tablet™



SPECIFICATIONS

IMPACT DOT MATRIX

Print Method: 9 -pin serial, USB, Ethernet
impact dot matrix

Print Font: 7 x 9/9 x 9

Print Speed: 4.7 lps (at 40 columns),
6.0 lps (at 30 columns)

Column Capacity: 40/42 or 33/35

Character Size: 1.2 (W) x 3.1 (H)/1.6 (W)
x 3.1 (H) mm

Characters per inch: 17.8/16 cpi or
14.5/13.3

GENERAL INFORMATION

Interface: RS-232C, IEEE 1284 parallel,
RS-485; 10/100Base-T/TX

Power: 24 V

Power Supply: PS-180

Weight: 5.5 lbs

Color: Epson Dark Gray, Epson Cool White

Dimensions: 160 (W) x 286 (D) x 138.5 (H)



SPECIFICATIONS

THERMAL PRINTER

Print Method: Thermal Line Printing

Print Speed Paper: Max. 11.8"/sec (300mm)
graphics and text; 2.4"/sec for ladder and 2D
barcodes

Dimensions: 80mm: 79.5 ± 0.5 (W) x 83mm
diameter (3.13" ± 0.02" x 3.27")

58mm: 57.5 ± 0.5 (W) x 83mm diameter (2.26"
± 0.02" x 3.27")

RELIABILITY

MTBF: 360,000 hours

MCBF: 70,000,000 lines

Autocutter: 2 million cuts

GENERAL INFORMATION

Interface: Built-in USB interface plus another
selection: serial RS-232C, parallel IEEE-1284,
high-speed USB, powered USB, Ethernet
10/100Base-T/TX, 802.11b/g/n (2.4GHz) and
802.11a/n (5GHz) or Bluetooth 2.1 + EDR

Power: 24VDC ± 7%

Power Consumption: Approx 1.8A (mean)

Power Supply: External power by the
Universal Printer Base

Dimensions: 4.92" x 7.64" x 4.49" (125 x 194
x 114mm)

Weight: 3.5 lbs

Color: Epson Dark Gray, Epson Cool White

Driver Support: Microsoft® Windows 7, Vista,
XP, 2000, Mac OS X® v10.4, v10.5, v10.6
(Power PC/Intel Processor), Linux



SPECIFICATIONS

MOBILE PRINTER

Print Method: Thermal Line Printing

Print Speed: Max. Receipt version 100mm/sec

RELIABILITY

MCBF: 10 million printing lines

GENERAL INFORMATION

Interface: 802.11b/g/n (2.4GHz) Wifi
and 802.11a/n (5GHz) Wifi or Bluetooth
3.0 (EDR supported)

Power: Custom Lithium-ion battery pack, AC
adapter (option)

Power Saving: Auto power-off function, WiFi
power-saving function

Dimensions: 3.11" x 4.71" x 1.71" (79.0 x
119.8 x 43.6mm) (W x D x H)

Weight: Receipt version: 0.5lbs (228g) with
battery, without roll paper and belt clip

Color: Epson Black

Supported Mobile: iOS, Android and Windows

Operating Systems: (Security Level WEP,
WPA, WPA2-Personal/Enterprise)