

Touch Dynamic

# CS200

All-in-One



CS200 All-in-One

## Highlights

- 4 Serial Ports, Powered
- 6 USB 2.0 Ports
- Speed and Reliability in a POS Terminal
- Serviceable Design
- CPU's up to Pentium IV 2.8Ghz

## Features

- 250W Power Supply
- 15" Bright LCD w/0°-70° Viewing Angle
- Elo Resistive Touch Screen
- Intel Chipset
- 24V Printer Power Port

## Optional

- Integrated Credit Card Reader
- Integrated Digital Persona UareU
- Integrated Wireless 802.11b/g
- Integrated 12" Rear LCD
- Integrated Pole Display
- Integrated CDRW/DVD Combo or DVD-R



**TOUCH DYNAMIC**  
IMPROVING TOUCH TECHNOLOGY

Touch Dynamic, Inc • 17 Camptown Road • Irvington, New Jersey 07111  
888.508.6824 • [www.touchdynamic.com](http://www.touchdynamic.com)

# Touch Dynamic CS-200 All-in-One Data Sheet

CPU Support	Celeron 2.0Ghz, Pentium IV 2.4Ghz, Pentium IV 2.8Ghz
Chipset	Intel 852GME (GMCH Memory Control Hub) and ICH4
System Memory	Supports 2xDDR DIMM 266/333 256MB RAM up to 2GB RAM
Graphic Memory	UMA Shared memory up to 64MB
<b>LCD / Touch Panel</b>	
LCD Size	15" TFT
Brightness (cd/m2)	250-350
Maximum Resolution	1024x768
Touch Screen Type	ELO Resistive
Tilt Angle (Degree)	0-70
<b>Storage</b>	
HDD	3.5" 80GB HDD (Optional: 2 x 2.5" Hard Drives)
Optical Drive	1xSlim CDRW / DVD or DVDRW
Flash Memory	Compact Flash (Type I & II)
RAID	Raid 0,1 (optional)
<b>Expansion</b>	
Mini-PC Socket	1
<b>External I/O Ports</b>	
PS/2 Keyboard & PS/2 mouse	1 shared port with splitter
USB	6 USB 2.0 Ports
Serial/COM	4xPowered COM ports ( pin1 / pin 9 support +5V / +12V by jumper)
Parallel	1 DB25
LAN (10/100)	1 RJ45 RTL8139
2nd VGA	1 male type connector with power
Cash Drawer Port	1 (12V / 24V)
Internal Speaker	2x2Watt
Audio	Optional Line out, mic in
Printer Port	24V Printer power port with cable
<b>Control Indicator</b>	
Power Indicator	1
Indicator LED	2 ( power, HDD)
<b>Power</b>	
Power Supply	250W Delta power supply
<b>Environment</b>	
EMC & Safety	FCC Class A, CEMark, LVD
Operating Temperature	5°C ~ 35°C (41°F ~ 95°F)
Storage Temperature	-20°C to 60°C
Operating Humidity	20% - 80% RH non condensing
Storage Humidity	20% - 85% RH non condensing
<b>Peripheral Input Device (optional)</b>	
Magnetic Card Reader	3 Tracks (RS-232 / PS2 Interface)
Biometric	Integrated Digital Persona UareU 4000B
<b>Peripheral Output Device</b>	
Second Display	12.1" TFT LCD
Customer Display	VFD / LCD
Dimension (WxDxH)	14.9 x 14.3 x 14.1 in
Weight	N.W. 20lbs / G.W. 28lbs
OS Support	Windows XP, WePOS, XP Embedded, XP Professional for Embedded, WIN 2000 Pro Embedded, Vista, Win NT 4.0, Linux, Redhat 7.2



**CS200**  
Rear View with  
Ports shown



**CS200**  
Side View