


HIGHLIGHTS



2x HDMI Outputs (Optional 3rd)



0/2/4x HDBaseT Outputs



Cable-less Design



Supports up to 3 Displays Simultaneously



Supports HDMI-CEC & EDID Emulation



Up to 300FT Transmission with HDBaseT

SPECIFICATIONS

MOTHERBOARD

Processors:

Intel® Celeron™ Elkhart Lake J6412 up to 2.6 Ghz

System Memory: 4GB DDR4

Graphic Engine: Intel® 10th UHD

STORAGE

Solid State Drive: Standard 128 GB m.2 SSD (SATA and NVMe Support)

EXTERNAL I/O PORTS

Front Side:

2x USB x2.0 (Type A)

Rear Side:

4x USB 3.0 (Type A)

2x HDMI (3rd Optional)

2x HDBaseT (Optional HDMI Capablity Only)

2x LAN PoE Support (Optional)

1x Comm

1x Line-out

1x Mic In

EXPANSION

Wireless 802.11 LAN (Optional)

OPTIONAL PERIPHERALS

VESA Wall mount/Wall mount kit 75 & 100 Supported

TECHNICAL SPECS

Dimensions: 10.6"(W) x 5.7" (H) x 1.6"(D)

Weight: 5LBS

Operating Temperature: 32°F ~ 95°F

Storage Temperature: -4°F ~ 140°F

Humidity: 20% ~ 85% noncondensing

POWER

65W/19V

OS SUPPORT

Win IOT Enterprise

